CERTIFIED RECORD OF LAND CORNER MONUMENTATION

¼ Corner to Sections 17 & 20, T15S R29E, W.M.

History of original corner establishment: Set by S.W. Lackland under his Contract No. 384 dated March 29, 1881 His Notes state: Set post with pits and mound for ¼ Sec Cor. From which:

A Pine 28 in. dia. bears N78°W 17 lks. dist.

DIAGRAM

T15S R29E

¼ S17 / S20

1982

RLS 934

Description of corner evidence found:

Found OBT, a badly rotted P. Pine stump, 28" diam., 24" high, badly weathered face showing, with scribes "DT" visible, bears N78°W 17 lks. = 11.22 ft. (Rec.)

Description of monument and accessories I established to perpetuate the original location of this corner:

At record bearing and distance from Fnd. O.B.T. stump I set a 3"x30" Al. Pipe with a 3½" Al. Cap, stamped as shown above, 10" above ground, with mound of stones around it. My new BT's are as follows:

A 9½" D.B.H. P. Pine, scribed "¼ S17 BT" bears N32°W, 23.1 ft.

A 8½" D.B.H. P. Pine, scribed "¼ S20 BT" bears S39°W, 42.1 ft.

Date Set: 9-8-82

Witness: Dale Wright, Luis McLind

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON JULY 17, 1970 VICTOR M. McLIND 934

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 14 day of Dec, 19 82

Robert D. Bagett by

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

N-7