CERTIFIED RECORD OF LAND CORNER MONUMENTATION

SEC. CORNER TO SECTIONS 16, 17, 20 & 21, T15S, R29E, W.M.

History of original corner establishment: SET BY S.W. LACKLAND UNDER HIS CONTRACT No. 384 DATED MARCH 29, 1887. HIS NOTES STATE: SET STONE 16x4x4 IN MOUND OF STONE FOR COR. TO SECS. 16, 17, 20 & 21.

A PINE 18" DIA, BEARS N81°E 20 LKS. DIST.

A PINE 14" DIA. BEARS S74°W 21 LKS. DIST.

DIAGRAM

T15S R29E

S17	S16
S20	S21

1982

RLS 934

Description of corner evidence found:

NO RELIABLE EVIDENCE FOUND.

BOTH OBT'S ARE LYING ON GROUND BUT BOTH HAVE BEEN DISTURBED BY CAT WORK IN AREA. (GRAVEL PIT)

Description of monument and accessories I established to perpetuate the original location of this corner:

I SET CORNER BY DOUBLE PROPORTIONMENT. AT CALCULATED POSITION I SET A 3"x30" AL. PIPE WITH A 3½" AL. CAP STAMPED AS SHOWN ABOVE, 12" ABOVE GROUND IN STONE MOUND, NEAR BOTTOM OF OLD GRAVEL EXCAVATION. MY NEW BT'S ARE AS FOLLOWS:

A 6½" D.B.H. LODGEPOLE PINE, SCRIBED "T15S R29E S20 BT" BEARS S17½°W, 12.1 FT.

A 6½" D.B.H. LODGEPOLE PINE, SCRIBED "T15S R29E S21 BT" BEARS S44°E, 28.1 FT.

A 6¼" D.B.H. P. PINE, SCRIBED "T15S R29E S16 BT" BEARS N41°E, 26.1 FT.

A 11" D.B.H. P. PINE, SCRIBED "T15S R29E S17 BT" BEARS N80°W, 91.3 FT.

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON
JULY 17, 1970
VICTOR M. McLIND
934

DATE SET: 10-6-82

WITNESS: DALE WRIGHT, LUIS McLIND

Office of Surveyor County of Grant

State of Oregon. I hereby certify that the within instrument was filed in this office for record on the 16 day of Dec, 19 82

Robert D. Bagett by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆ GPO—798-276