CERTIFIED RECORD OF LAND CORNER MONUMENTATION

ORIGINAL LINE TREE BETWEEN SECTIONS 20 & 21, T15S, R29E, AND 25.48 CH. SOUTH FROM SEC. COR. 16, 17, 20 & 21

History of original corner establishment: SET BY S.W. LACKLAND UNDER HIS CONTRACT NO. 384 DATED MARCH 29, 1881.

HIS NOTES STATE: NORTH BETWEEN SECS. 20 & 21 —

54.52 A PINE 14 IN. DIA.

80.00 SET STONE 16x4x4 INS. IN MOUND OF STONE FOR COR. TO SECS 16, 17, 20 & 21.

DIAGRAM



Description of corner evidence found:

FOUND ORIGINAL LINE TREE, NOW A 15½" PINE WINDFALL WITH 2 HACKS ABOUT 10" APART, ON BOTH N. & S. SIDES OF TREE.

Description of monument and accessories I established to perpetuate the original location of this corner:

AT LOCATION FORMERLY OCCUPIED BY LINE TREE I SET A 3"X 30" ALUMINUM PIPE WITH A 3½" AL. CAP STAMPED ⟶ T15S R29E WP S20 | S21 1982 RLS 934

I ESTABLISHED 2 NEW BT'S AS FOLLOWS:

A 14½" DBH D. FIR, MARKED WITH AN "X" AT BR. HEIGHT AND "BT" SCRIBED ON A LOW BLAZE, BEARS N47°E, 24 FT.

A 13" DBH D. FIR, MARKED SAME AS ABOVE BT, BEARS N 7½°W, 29 FT.

I SET A STEEL POST W/SIGN 54-4, 3' N. OF AL. CAP.

REGISTERED PROFESSIONAL LAND SURVEYOR

Victor M. McLind

OREGON JULY 17, 1970 VICTOR M. McLIND 934

DATE SET: 10-6-82

WITNESS: DALE WRIGHT, LUIS MCLIND

Office of Surveyor County of Grant

State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 6 day of Dec, 19 82 at 2 o'clock P M and recorded in book

Edward D. Bagett by

(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

O 1/4 - 9