CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P Mc Cornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 14 x 12 x 8 ins. 10 ins in the ground for cor. to sec. 19, 24, 25 & 30, marked with 4 notches on N and 2 notches on the South edges and raised a mound of stone alongside. Pits inpractical.
(Note: This line re-surveyed by Henry W. Cooke in 1884, Under Gerneral Land office Contract No. 512, where he set corners for T15S R37E)

DIAGRAM

T15S
R36E R37E
S24
S25
1983
PLS 848

Description of corner evidence found:

Found 18" x 13" x 8" stone with 4 notches on North & 2 notches on South.
Set 8" in the ground, with a mound of stone alongside.
No accessories originaly established.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with 3½" aluminum cap stamped as shown in diagram.
Set 14" in the ground, set original stone South alongside pipe & raised a mound of stone around pipe.
From which:
A Juniper 9" dia. bears N23°W, 5.6 ft. scribed T15S R36E S24 BT.
A Juniper 10" dia. bears S44°W, 22.5 ft. scribed T15S R36E S25 BT.
Set steel post with warning signs 3 ft. West.
Nailed brass washers stamped PLD 848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date June 17. 1983

Witnessed by D Mitchell Ferguson

Office of....Surveyor..... *County of*.....Grant.....
State of..Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*..29th... *day of*.....August....., 1983..
..... by .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

R-25