CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. Mc Cornack, under General Land Office Contract No. 398. Surveyors Generals Notes State: Set basalt stone 20 x 14 x 6 ins. 15 ins. in the ground for ¼ sec. corner marked ¼ on W face.
From which:
A Pine 24 ins. diam. bears S25°E, 461ks dist. marked ¼ S BT.
A Pine 24 ins. diam. bears N5°W, 87 1ks dist. marked ¼ S BT.

DIAGRAM

T15S R36E
¼
S26 | S25
1983
PLS 848

Description of corner evidence found:

Found 16" x 14" x 8" stone, no marks visible, a old cluster of stone alongside.
From which
A Pine 27" dia. live in good condition, with scribing reads ¼ S bears N5°E (record N5°W) 56.4 ft. to blaze face.
A Pine 23" dia. live in good condition, with scribing reads S, bears S25°E, 30.0 ft. to face of blaze.
Accepted stone as ¼ cor. position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" x 2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 18" in the ground & raised a mound of stone around pipe.
From which:
A Pine 27" dia. (original bearing tree) bears N5°E, 58.0 ft new scribing reads ¼ S25 BT (this was originaly, record N5°W, sec. 26 BT.)
A Fir 8" dia. bears S75°W, 9.2 ft. scribed ¼ S26 BT.
Set a steel post with warning sign North 2.0 ft.
Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date June 10, 1983

Witness No Witness

Office of.....Surveyor..... *County of*.....Grant.....
State of...Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*.....29th..... *day of*.....August....., *19*...83.
..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆GPO—798-276

T-21