CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. McCornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 18x12x6" 12" in the ground for corner to section 25,26,35,&36 marked with 1 notch on the S and 1 notch on the E face, and raised a mound of stone alongside.

DIAGRAM

T15S R36E
S26 | S25
S35 | S36
1983
PLS848

Description of corner evidence found:

No evidence found, corner falls on rocky ground near fence corner.
There are many stones of call size in the area, with only one notch on 2 faces, nothing could be recovered.
No accessories originally established.
Set corner by proportion.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 12" in the ground & raised a mound of stone around the pipe.
From Which:
A Pine 15" dia. bears N53°W, 42.0 ft. scribed T15S R36E S26 BT.
A " 9" " " N10°E, 29.8 ft. " " " S25 BT.
A " 13" " " S44°E, 44.9 ft. " " " S36 BT.
A " 8" " " S31½°W, 66.5 ft. " " " S35 BT.
Set steel posts with warning & boundry signs East 5 ft. And South 5 ft.
E-W fence North 10 ft.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree,

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1969
DOUGLAS M. FERGUSON
848

Corner monumented 6-23-83
Witnessed by Mollee Ferguson

Office of.....Surveyor..... *County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*.....29th *day of*.....August....., *19*.....83.
.....Robert D Bazett..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

V-21