CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. McCornack, Under General Land Office Contract No. 398. Surveyor Generals Notes State: Set basalt stone 30x7x4" 22" in the ground for ¼ section corner marked ¼ on W face and raised a mound of stone alongside.

DIAGRAM

T15S R36E

S35 | ¼ S36

1983

PLS848

Description of corner evidence found:

Found a 27"x7"x4" stone lying down with an old mound of stone alongside.
It appears that this corner has been protected, even though a fence runs through corner.
No accessories originally established.
Accepted the stone as the ¼ corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30"x2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 15" in the ground, set original stone South alongside pipe & raised a mound of stone around pipe.
From Which:
A Juniper 5" dia. bears N14°50'W, 87.9 ft. scribed ¼ S35 BT.
A Pine 13" dia., at base & forked 3 ways, bears N26°20'E, 73.1 ft. scribed ¼ S36 BT.
Set steel posts with warning & boundry signs 7' North & 7' South from corner.
Nailed brass washers stamped PLS848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Corner Monumented 6-23-83

Witnessed by Mollee Ferguson

Office of.....Surveyor..... *County of*.....Grant.....

State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*..29th *day of*.....August....., *19*..83.

.....
(COUNTY OFFICIAL)

..... *by* .....
(DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

X-21