CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1881 by Eugene P. Mc Cornack, under General Land Office Contract No 398. Surveyor Generals Notes State: Set basalt stone 18 x 12 x 10 ins. 12 ins in the ground for standard cor. to secs. 35 & 36, marked SC with 1 notch on E and 5 notches on W edges.
From whihh:
A Pine 14 ins. diam. bears N25°W, 38 lks dist. marked T15S R36E S35 BT.
No other trees within limits.
Raised a mound of stone alongside.

DIAGRAM

SC
T15S R36E
b S35 | S36
T16S
1983
PLS 848

Description of corner evidence found:

Found 20" x 15" x 10" stone, notches visible, set in a mound of stone, alongside a fence corner.
From which:
A Pine 40" diam. live in good condition with scribing viisible bears N39°W, 26.6 ft. to face of blaze (record N25°W, 25.1)
Accepted position of stone as standard corner position.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 30" x 2" aluminum pipe with a 3½" aluminum cap stamped as shown in diagram.
Set 26" in the ground, set original stone South alongside pipe.
From which:
A Pine (the original bearing tree) 40" dia. bears N39°W, 27.3 ft. new scribing, below old blaze, reads T15S R36E SC S35 BT.
A Mahogany 6" dia. bears N53°E, 18.3 ft. scribed T15S R36E SC S36 BT.
S t steel post with warning & boundary signs North 5 ft.
Nailed brass washers stamped PLS 848, bearing tree & warning signs to each tree.

REGISTERED PROFESSIONAL LAND SURVEYOR
OREGON
JULY 12, 1968
DOUGLAS M. FERGUSON
848

Date June 29, 1983

Witnessed by D. Mitchell Ferguson

Office of.....Surveyor..... *County of*.....Grant.....
State of.....Oregon....., *I hereby certify that the within instrument was filed in this office for record on the*...29th*day of*.....August....., *19*...83.
Robert D. Rogers..... *by* .....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

GPO—798-276

Z-21