

RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 7, T.16S., R.26E., W.M.

ORIGINAL SURVEY BY: Jasper Wilkins

CONTRACT NUMBER: 189

CONTRACT DATE: June 21, 1873

SUBSEQUENT SURVEY: C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION:

Set Mile Stone 6x12x14 for Cor Secs 1-6-7 and 12

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 350): SEE RECORD MAP OF SURVEY NO. 58.

Point for the cor. of secs. 1, 6, 7, and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 16 S	
R 25 E	R 26 E
S 1	S 6
S 12	S 7
1959	

from which

A pine, 8 ins. diam., bears N. 29° E., 26 lks. dist.,
mkd. T16S R26E S6 BT.

A pine, 9 ins. diam., bears S. 50° E., 10 lks. dist.,
mkd. T16S R26E S7 BT.

A juniper, 6 ins. diam., bears S. 25½° W., 37 lks. dist.,
mkd. T16S R25E S12 BT.

A juniper, 6 ins. diam., bears N. 56¼° W., 38 lks. dist.,
mkd. T16S R25E S1 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

January 9, 2017

**RECEIVED AND FILED
GRANT COUNTY SURVEYOR**

JAN 30 2017

BY: _____



EXPIRES: 6/30/2018