

RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 10, T.16S., R.26E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEY: C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 14x12x4 for cor. to secs. 3, 4, 9, & 10.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 380-381); SEE RECORD MAP OF SURVEY NO. 58.

A spurious cor. of secs. 3, 4, 9 and 10, bears West, 2.03 chs. dist., monumented with a basalt stone, 14 x 12 x 4 ins., loosely set in a small mound of stone, recently marked with 3 grooves on one side. This point has been locally used as the sec. cor.

Point for the cor. of secs. 3, 4, 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T	16	S	R	26	E
	S	4	S	3	
	S	9	S	10	
	1960				

from which

A juniper, 14 ins. diam., bears N. 18° E., 76 lks. dist.,
mkd. T16S R26E S3 BT.

A juniper, 6 ins. diam., bears S. 25° E., 10 lks. dist.,
mkd. T16S R26E S10 BT.

A pine, 8 ins. diam., bears S. 36° W., 171 lks. dist.,
mkd. T16S R26E S9 BT.

A juniper, 6 ins. diam., bears N. 39° W., 114 lks. dist.,
mkd. T16S R26E S4 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251



January 9, 2017

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

JAN 27 2017

BY:

[Handwritten signature]



EXPIRES: 6/30/2018