

RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 16, T.16S., R.26E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEY: C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 14x12x8 for cor. to secs. 8, 9, 16 & 17.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 391): SEE RECORD MAP OF SURVEY NO. 58.

Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 16 S R 26 E
S 8 | S 9
S 17 | S 16
1960

from which

A pine, 10 ins. diam., bears N. 56° E., 37 lks. dist., mkd. T16S R26E S9 BT.

A pine, 10 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ E., $32\frac{1}{2}$ lks. dist., mkd. T16S R26E S16 BT.

A pine, 14 ins. diam., bears S. 26° W., 38 lks. dist., mkd. T16S R26E S17 BT.

A pine, 32 ins. diam., bears N. 38° W., 72 lks. dist., mkd. T16S R26E S8 BT.

From this point the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., bears S. $89^{\circ} 07'$ W., 157.75 chs. dist., heretofore described.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:


Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251


January 9, 2017

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

JAN 30 2017

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018