

# RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 23, T.16S., R.26E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEY: C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 18x10x8 for cor. to secs. 14, 15, 22 & 23.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 364): SEE RECORD MAP OF SURVEY NO. 58.

The cor. of secs. 14, 15, 22, and 23, monumented with a basalt stone, 12 x 12 x 2 ins., set 4 ins. in the ground, mkd. with 2 grooves on E. face and 3 grooves on S. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

|      |      |      |
|------|------|------|
| T 16 | S R  | 26 E |
| S 15 | S 14 |      |
| S 22 | S 23 |      |
| 1959 |      |      |

from which

A pine, 40 ins. diam., bears N.  $35^{\circ}$  E., 23 lks. dist., mkd. T16S R26E S14 BT.

A pine, 15 ins. diam., bears S.  $32\frac{1}{2}^{\circ}$  E., 83 lks. dist., mkd. T16S R26E S23 BT.

A pine, 7 ins. diam., bears S.  $44^{\circ}$  W., 54 lks. dist., mkd. T16S R26E S22 BT.

A pine, 6 ins. diam., bears N.  $55^{\circ}$  W., 24 lks. dist., mkd. T16S R26E S15 BT.

Deposit original corner stone alongside iron post.

## EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

## PREPARED BY:


Michael C. Springer, PLS  
Grant County Surveyor  
Marcus Teague, Technician

217 N. Canyon Blvd.  
John Day, OR, 97845  
(541) 575-1251

January 9, 2017

RECEIVED AND FILED  
GRANT COUNTY SURVEYOR

JAN 27 2017

BY: 

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

  
OREGON  
JULY 9, 2002  
MICHAEL C. SPRINGER  
#70918

EXPIRES: 6/30/2018