

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment

Original corner established by L. C. Stratton P.E. 4563 in 1962, during survey filed with Grant County as Map of Survey 67. Map indicates that corner was monumented during that survey but contains no other information.

E 1/16
C . C
S19
ORE 4563

P-4
WCS 09 B. 1 Pg. 33

Description of corner evidence

At assumed corner location found 2-1/2 ins. O. D. galvanized iron pipe with 2-1/2 ins. brass cap marked as shown in diagram up 18 ins. above ground in center of 3 feet diam. stone mound.

Corner Monumentation

Accepted position of found monument as described. Set aluminum "C" channel post 5 feet East of cap and attached signs 54-2 and 54-9 to post facing cap.

Marked bearing trees

A 9 ins. Ponderosa Pine bears North 15° East, 9.9 feet, scribed -X- at breast height- BT;
an 11 ins. Ponderosa Pine bears South 68-1/2° West, 44.8 feet, scribed -CE 1/16 S19 BT.

Nailed tacks with brass washers stamped-ASE LS1026- to faces and nailed Bearing Tree signs (54-3) and Land Survey Monument signs (54-9) to bearing trees. Painted 6 ins. wide red band 6 feet above ground and faces of all bearing trees red. Bearings by staff compass declination 18° East. Distances to bearing trees are measured to center side of bearing tree marked by a magnetic nail about one foot above ground on the right side facing the tree.

WGS 84 Geodetic position:
Latitude: 44°10'09.84429" N
Longitude: 119°38'33.31827" W

I hereby certify that the above corner monument was re-established as herein described on June 22, 2010.

Witnesses: Jon Ryan
Todd Catterson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

8/30/10 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026

RENEWS 12/31/11

Office of Surveyor, County of Grant, State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 7 day of SEPT., 2010.

[Signature] by _____
COUNTY OFFICIAL DEPUTY

Cross Index P-4
C.S.1899