

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment

Original corner established by Alonzo Gesner, Deputy Surveyor, under General Land Office Contract No. 206 dated July 10, 1874, Surveyor General's records state:
South 89°54' West on true line between sec's. 28 and 29
39.93 Set stone 12 X10 X 6 for ¼ sec. cor..

$$\begin{array}{r} 1 \quad S21 \\ 4 \quad S28 \\ \hline T16S R26E \\ 1960 \end{array}$$

Corner re-established by survey by C. Albert White, BLM Cadastral Surveyor, under Group 359 Oregon dated October 18, 1957 and approved May 1, 1962, BLM records state:
N. 89°19' W., bet. Secs. 21 and 28.

R-11
WCS 09 B. 1 Pg. 20

39.90 Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28 ins. long, 2-1/2 ins. diam., 24 ins. in the ground with brass cap mkd. -¼ S21/S28 T16S R26E 1960- from which a pine, 8 ins. diam., bears N. 20-1/2° W., 11 lks. dist., mkd. ¼ S21 BT. a pine 10 ins. diam. bears S. 0-1/2° W., 32 lks. dist. mkd. ¼ S28BT.

Description of corner evidence

At assumed corner location found 2-1/2 ins. O. D. galvanized iron pipe with 3-1/4 ins. brass cap marked as shown in diagram up 9 ins. above ground. Found White's BT's: a 15 ins. Ponderosa Pine standing dead with top broken out bears South 01° East a distance of 21.6 feet, healed blaze; a 15 ins. Ponderosa Pine bears North 22° West a distance of 7.1 feet, healed blaze.

Corner Monumentation

Set aluminum "C" channel post 5 feet North of cap and attached sign 54-9 to post facing cap.

Marked bearing trees

An 11 ins. Ponderosa Pine bears North 45-1/2° East, 36.4 feet, scribed -1/4 S21 XBT; a 7 ins. Ponderosa Pine bears South 42-1/2° East, 61.3 feet, scribed -1/4 S28 BT; a 12 ins. Ponderosa Pine bears South 49-1/2° West, 34.2 feet, scribed -X- at breast height- BT.

Nailed tacks with brass washers stamped-ASE LS1026- to faces and nailed Bearing Tree signs (54-3) and Land Survey Monument signs (54-9) to bearing trees. Painted 6 ins. wide red band 6 feet above ground and faces of all bearing trees red. Bearings by staff compass declination 18° East. Distances to bearing trees are measured to center side of bearing tree marked by a magnetic nail about one foot above ground on the right side facing the tree

WGS 84 Geodetic position:
Latitude: 44°09'45.40453" N
Longitude: 119°36'27.23264" W

I hereby certify that the above corner monument was re-established as herein described on May 27, 2010.

Witnesses: Jon Ryan
Todd Catterson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

8/30/10 OREGON
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026

RENEWS 12/31/11

Office of Surveyor, County of Grant, State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 7 day of SEPT, 2010.

Mal Sp by _____
COUNTY OFFICIAL DEPUTY