

RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 27, T.16S., R.26E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEY: C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 18x10x8 for cor. to secs. 21, 22, 27 & 28.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 373-374): SEE RECORD MAP OF SURVEY NO. 58.

Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone, $4\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T	16	S	R	26	E
	S	21	S	22	
	S	28	S	27	
	1960				

from which

A juniper, 20 ins. diam., bears N. 72° E., 114 lks. dist., mkd. T16S R26E S22 BT:

A juniper, 33 ins. diam., bears S. 81° E., 123 lks. dist., mkd. T16S R26E S27 BT.

A juniper, 6 ins. diam., bears S. 44° W., 443 lks. dist., mkd. T16S R26E S28 BT.

A pine, 14 ins. diam., bears N. 2° W., 857 lks. dist., mkd. T16S R26E S21 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

January 9, 2017

**RECEIVED AND FILED
GRANT COUNTY SURVEYOR**

JAN 27 2017

BY:

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018