


CORNER RESTORATION

CORNER: NW Cor. Sec. 3 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: *Intersect 3rd Standard "S" 9.87 chs. W. of Cor. to Sec's 33 & 34 T15S R27E. At which point I set basalt Stone 18x14x10 ins. 14 ins in ground for C Cor. to Sec's 3 & 4. Marked with 3 notches on E and 3 notches W on edges and CC on S. face. Raised Mound of Stone 3 ft. high 6 ft. base, alongside.*

► 1975:

The original closing cor. of secs. 3 and 4, monumented with a basalt stone, 18 x 10 x 6 ins., firmly set 12 ins. in the ground, and in a mound of stone, 4 ft. base, 1½ ft. high, with 3 notches on E. and W. edges. I add marks AM to the original stone.

Intersect the Third Standard Parallel South.

True point for the closing cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 15 S R 27 E
S 33
S 4 | S 3
T 16 S R 27 E
C C
1976

from which

A juniper, 10 ins. diam., bears S. 59° W., 407 lks. dist., mkd. T16S R27E S4 CC BT.

No other suitable tree available within limits.

From this point, the standard cor. of secs. 33 and 34, T. 15 S., R. 27 E., bears S. 89° 39' E., 10.01 chs. dist., hereinbefore described.


RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 3 2010

BY:



EXPIRES: 6/30/2012

November 30, 2010

Grant County Surveyor

EVIDENCE FOUND: None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 889 filed in the office of the Grant County Surveyor.