

# RECORD OF LAND CORNER MONUMENTATION


CORNER: W $\frac{1}{4}$  Cor. Sec. 6 Only, T.16S., R.27E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEYS: Samuel W. Lackland 1881, C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 10x10x8 for  $\frac{1}{4}$  sec. cor.

1881 RESURVEY BY SAMUEL W. LACKLAND, DEPUTY SURVEYOR UNDER CONTRACT NO. 415 DATED 08/19/1881.

Set Basalt stone 17x12x8 ins 10 ins in ground for  $\frac{1}{4}$  sec cor marked  $\frac{1}{4}$  on W face. Raised mound of stone 2 ft high 4 ft base alongside.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 343): SEE RECORD MAP OF SURVEY NO. 58.

Point for the  $\frac{1}{4}$  sec. cor. of sec. 6 only, on the W. bdy. of sec. 6, T. 16 S., R. 27 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 14 ins. in the ground to bedrock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.

$\frac{1}{4}$   
S 6  
T 16 S  
R 27 E  
1959

from which

A juniper, 5 ins. diam., bears N. 84° E., 115 lks. dist., mkd. X only.

A juniper, 15 ins. diam., bears S. 56° E., 123 lks. dist., mkd.  $\frac{1}{4}$  S6 BT.

## EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

## PREPARED BY:

Michael C. Springer, PLS  
Grant County Surveyor  
Marcus Teague, Technician

217 N. Canyon Blvd.  
John Day, OR, 97845  
(541) 575-1251

January 10, 2017

RECEIVED AND FILED  
GRANT COUNTY SURVEYOR

JAN 27 2017

BY: 

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

  
OREGON  
JULY 9, 2002  
MICHAEL C. SPRINGER  
#70918

EXPIRES: 6/30/2018