

RECORD OF LAND CORNER MONUMENTATION


CORNER: NW Cor. Sec. 7 Only, T.16S., R.27E., W.M.

ORIGINAL SURVEY BY: Alonso Gesner

CONTRACT NUMBER: 206

CONTRACT DATE: July 10, 1874

SUBSEQUENT SURVEYS: Samuel W. Lackland 1881, C. Albert White 1957



ORIGINAL G.L.O. DESCRIPTION: Set stone 30x18x8 for cor. to secs. 1, 12, 6 & 7 from which a pine 36 in. dia. bears S86°W. 42 lks.

1881 RESURVEY BY SAMUEL W. LACKLAND, DEPUTY SURVEYOR UNDER CONTRACT NO. 415 DATED 08/19/1881.

Set Basalt stone 18x14x7 ins 12 ins in ground for cor to secs 6 & 7, marked with 5 notches on S & 1 notch on N edges. Raised mound of stone alongside.

1957 RESURVEY BY C. ALBERT WHITE, CADASTRAL SURVEYOR UNDER SPECIAL INSTRUCTIONS DATED 10/3/1957 INCLUDED UNDER GROUP NO. 359 (Pg. 342): SEE RECORD MAP OF SURVEY NO. 58.

Point for the corner of secs. 6 and 7 only, on the W. bdy. of T. 16 S., R. 27 E., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 16 S		T 16 S
R 26 E		S 6
S 1		S 7
		R 27 E
1959		

from which

A pine, 10 ins. diam., bears N. $49\frac{1}{2}^{\circ}$ E., 53 lks. dist., mkd. T16S R27E S6 BT.

A pine, 6 ins. diam., bears S. $18\frac{1}{4}^{\circ}$ E., $8\frac{1}{2}$ lks. dist., mkd. T16S R27E S7 BT.

EVIDENCE FOUND:

None. No field visit was made for this Corner Restoration Report, it has been prepared from record General Land Office and Bureau of Land Management field notes. See Record Map of Survey 58 filed in the Grant County Surveyor's Office.

PREPARED BY:

Michael C. Springer, PLS
Grant County Surveyor
Marcus Teague, Technician

217 N. Canyon Blvd.
John Day, OR, 97845
(541) 575-1251

January 11, 2017

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

JAN 27 2017

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2018