


CORNER RESTORATION

CORNER: NW Cor. Sec. 22 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:
► Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set basalt Stone 18x12x7 ins. 14 ins. in ground for Cor. to Secs. 15, 16, 21 & 22. Marked 3 notches on S and 3 notches on E. edges. Raised Mound of Stone 3 ft. high 5 ft. base alongside.

► 1975: The cor. of secs. 15, 16, 21, and 22, monumented with the original basalt stone, 18 x 12 x 7 ins., firmly set 15 ins. in the ground, and in a mound of stone, 3 ft. base, 6 ins. high, mkd. with 3 grooves on E. face and 3 notches on S. edge.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 16 S R 27 E
S 16 S 15
S 21 S 22
1976

from which

A fir, 10 ins. diam., bears N. 8½° E., 162 lks. dist., mkd. T16S R27E S15 BT.

A ponderosa pine, 25 ins. diam., bears S. 35° E., 78 lks. dist., mkd. T16S R27E S22 BT.

A fir, 8 ins. diam., bears S. 1° W., 33 lks. dist., mkd. T16S R27E S21 BT.

A fir, 11 ins. diam., bears N. 47½° W., 149 lks. dist., mkd. T16S R27E S16 BT.

Deposit corner stone alongside iron post.

RESTORATION BY, STAMP AND DATE:
Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 15, 2010
BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

November 15, 2010 Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.