

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established of record

DIAGRAM

T16S R27E

C $\frac{1}{4}$ S22

Description of corner evidence found:

None

See Record Map of Survey No. 897

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2 $\frac{1}{2}$ x30 inch aluminum pipe with attached aluminum cap marked as shown, 26 inches in the ground, with mound of stone to top of cap. From which I scribe new BT's:

A Fir, 11 ins. diam. bears N. 61° E., 14.0 feet marked C $\frac{1}{4}$ S22 BT.

A Pine, 11 ins. diam. bears S. 17° E., 27.1 feet marked C $\frac{1}{4}$ S22 BT.

Corner set by: R. D. Bagett
Witnesses: J. L. Watson
T. R. Steele

Aug. 27, 1985

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Robert D. Bagett

OREGON
JULY 12, 1963
ROBERT D. BAGETT
598

Monument Marked

T16S R27E

C $\frac{1}{4}$. S22

1985

OPLS 598

Nailed brass washer marked OPLS 598 to lower blaze of new BT's. Painted 6" red band around new BT's above blaze and attached BT sign and attention sign to BT's. Set steel fence posts approx. 3 feet East from monument and attached appropriate signs as called for in my contract. Used magnetic compass with 20° E. var. and steel tape, distance measured at a 40d nail driven in the side center at root crown of new BT's.

Office of.....Surveyor.....County of.....Grant.....
State of.....Oregon....., I hereby certify that the within instrument was filed in this office
for record on the.....4.....day of.....Dec....., 19..1985
.....*Robert D. Bagett*.....by.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276