

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner not previously established

DIAGRAM

T16S R27E

C $\frac{1}{4}$ S23

Description of corner evidence found:

None

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Robert D Baggett

OREGON
JULY 12, 1963
ROBERT D. BAGETT
598

See Record Map of Survey No. 897.

Description of monument and accessories I established to perpetuate the original location of this corner:

At the corner point I set a 2 $\frac{1}{2}$ x30 inch aluminum pipe with aluminum cap marked as shown, 27 inches in ground, with mound of stone to top of cap
From which I scribe new BT's:

- A Fir, 12 ins. diam. bears N. 66° E., 28.4 feet
marked C $\frac{1}{4}$ S23 BT.
A Fir, 19 ins. diam. bears N. 40° W., 29.9 feet
marked C $\frac{1}{4}$ S23 BT.

Monument Marked

T16S R27E

C $\frac{1}{4}$ S23

1985

OPLS 598

Corner set by: R. D. Baggett
Witnesses: J. L. Watson
T. R. Steele

Aug. 29, 1985

Nailed brass washer marked OPLS 598 to lower blaze of new BT's. Painted 6" red band around new BT's above blaze and attached BT sign and attention sign to BT's. Set steel fence posts approx. 3 feet East from monument and attached appropriate signs as called for in my contract. Used magnetic compass with 20° E. Var. and steel tape distance measured to a 40d nail driven in the side center at root crown of new BT's.

Office of.....Surveyor..... County of.....Grant.....

State of.....Oregon....., I hereby certify that the within instrument was filed in this office

for record on the..... day of....., 19⁸⁵

Robert D Baggett by

(COUNTY OFFICIAL)

(DEPUTY)

Attest: *Mary Meulton*
Form R6-7100-57 (9/71)

☆U.S. GOVERNMENT PRINTING OFFICE-1983-793-276