


CORNER RESTORATION

CORNER: NW Cor. Sec. 28 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: *Set basalt Stone 18x16x7 ins. 14 ins. in ground for Cor to Sec's 28, 29, 20 & 21 Marked with 2 notches on S and 4 on E. edges. Raised mound of stone 2½ ft. high 5 ft. Base, alongside*

- 1975: Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock mkd. X, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

T 16 S R 27 E
S 20 S 21
S 29 S 28
1976

from which

A juniper, 15 ins. diam., bears N. 29½° E., 81 lks. dist., mkd. T16S R27E S21 BT.

A juniper, 23 ins. diam., bears S. 48½° E., 24 lks. dist., mkd. T16S R27E S28 BT.

A juniper, 21 ins. diam., bears N. 59° W., 40 lks. dist., mkd. T16S R27E S20 BT.


No other suitable tree available within limits.


RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 3 2010

BY: 



EXPIRES: 6/30/2012

November 30, 2010

Grant County Surveyor

EVIDENCE FOUND: None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 889 filed in the office of the Grant County Surveyor.