


CORNER RESTORATION

CORNER: NW Cor. Sec. 26 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set basalt stone 17x12x4 ins. 12 ins. in ground for Cor. to Secs. 26, 27, 22 & 23. Marked with 2 notches on S and 2 notches on E edges. Raised mound of Stone 3 ft. high and 5 ft. at base alongside

- 1975:

The cor. of secs. 22, 23, 26, and 27, monumented with the original basalt stone, 17 x 8 x 4 ins., firmly set 4 ins. in the ground, mkd. with 1 notch on E. and 2 notches on S. edges, and X on top.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 16 S R 27 E
S 22 | S 23
S 27 | S 26
1975

from which

A ponderosa pine, 17 ins. diam., bears N. 65° E.,
36 lks. dist., mkd. T16S R27E S23 BT.

A ponderosa pine, 12 ins. diam., bears S. 77° E.,
77½ lks. dist., mkd. T16S R27E S26 BT.

A ponderosa pine, 22 ins. diam., bears S. 3½° W.,
66½ lks. dist., mkd. T16S R27E S27 BT.

A ponderosa pine, 8 ins. diam., bears N. 53° W.,
120 lks. dist., mkd. T16S R27E S22 BT.

Deposit corner stone alongside iron post.

RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 12, 2010

BY: 



EXPIRES: 6/30/2012

November 12, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.