


CORNER RESTORATION

CORNER: NW Cor. Sec. 25 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set basalt stone 15x10x8 ins. 10 ins. in ground for Cor to Secs 25, 26, 24 & 23. Marked with 2 notches on S. and 1 notch on E and Raised Mound along side. From Which A Pine 28 ins. diam. bears N72°W 131 lks. dist. Marked T16S R27E S23 BT. A Pine 40 ins. diam. bears S35°W 71 lks. dist. Marked T16S R27E S26 BT

- 1975:

The cor. of secs. 23, 24, 25, and 26, monumented with an unmarked stone, 15 x 10 x 8 ins., loosely set in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees:

- A ponderosa pine, 47 ins. diam., bears S. 30° W., 71 lks. dist., with scribe marks R27E S26 visible on opened blaze. (Record, S. 35° W.)
- A sawed ponderosa pine stump, 37 ins. diam., bears N. 72° W., 128 lks. dist., with scribe marks BT visible on open blaze. (Record, and slope, 131 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 16 S R 27 E
S 23 | S 24
S 26 | S 25
1975

from which new bearing trees

- A fir, 17 ins. diam., bears N. 82½° E., 53 lks. dist., mkd. T16S R27E S24 BT.
- A ponderosa pine, 10 ins. diam., bears S. 49½° E., 24 lks. dist., mkd. T16S R27E S25 BT.
- A white fir, 13 ins. diam., bears N. 26½° W., 12½ lks. dist., mkd. T16S R27E S23 BT.

Deposit corner stone alongside iron post.

RESTORATION BY, STAMP AND DATE:
Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 12 2010
BY:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

November 11, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.