


# CORNER RESTORATION

CORNER: NW Cor. Sec. 33 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

**ORIGINAL DESCRIPTION:** Set basalt Stone 16x14x9 ins. 14 ins. in ground for Sec. Cor. to Sec's 28, 29, 32 & 33. Marked one notch on S. and 4 notches on E. edges. Raised Mound of Stone 3 ft. high 5 ft. base, alongside.

- 1975: Point for the cor. of secs. 28, 29, 32, and 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground, to solid rock mkd. X, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

|               |
|---------------|
| T 16 S R 27 E |
| S 29   S 28   |
| S 32   S 33   |
| 1976          |

from which

A juniper, 10 ins. diam., bears N. 16° E., 51 lks. dist., mkd. T16S R27E S28 BT.

A juniper, 18 ins. diam., bears N. 46½° W., 77 lks. dist., mkd. T16S R27E S29 BT.

and a bearing object

A basalt boulder, 4 x 4 x 10 ft., bears S. 6° E., 14 lks. dist., mkd. X BO.

No other suitable trees available within limits.

RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED  
GRANT COUNTY SURVEYOR

DEC 3 2010

BY: 



November 30, 2010

Grant County Surveyor

**EVIDENCE FOUND:** None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 889 filed in the office of the Grant County Surveyor.