


CORNER RESTORATION

CORNER: NW Cor. Sec. 34 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: *Set basalt Stone 16x7x5 ins. 12 ins. in ground for Cor. To Secs. 27, 28, 33 & 34. Marked with 1 notch on S and 3 notches on E edges. Raised Raised Mound of Stone 2½ ft. high, 4½ base, alongside.*

- 1975: cor. of secs. 27, 28, 33, and 34, monumented with inal basalt stone, 16 x 7 x 5 ins., loosely set i und of stone, 1½ ft. base, 6 ins. high, mkd. with ve on S. face and 3 notches on E. edge.

he corner point

an iron post, 28 ins. long, 2½ ins. diam., 18 ins he ground, to solid rock, and in a mound of stone . base, to top, with brass cap mkd.

T 16 S R 27 E
S 28 S 27
S 33 S 34
1975

which

A juniper, 13 ins. diam., bears N. 62¾° E., 147 lks. dist., mkd. T16S R27E S27 BT.

A juniper, 18 ins. diam., bears S. 33° E., 90 lk. dist., mkd. T16S R27E S34 BT.

A juniper, 11 ins. diam., bears S. 6¾° W., 109 lks. dist., mkd. T16S R27E S33 BT.

No other suitable tree available within limits.


Deposit corner stone alongside iron post.

RESTORATION BY, STAMP AND DATE:


Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 15, 2010

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

November 15, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.