


CORNER RESTORATION

CORNER: NW Cor. Sec. 35 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set basalt stone 20x12x6 ins. 14 ins. in ground for Cor. to Secs. 26, 27, 34 & 35. Marked with 2 notches on E and 1 notch on S edges. Raised mound of Stone 2½ ft. high and 5 ft. at base alongside

► 1975:

The cor. of secs. 26, 27, 34, and 35, monumented with the original basalt stone, 18 x 12 x 7 ins., firmly set 8 ins. in the ground, mkd. with 1 notch on S. edge, and 2 grooves on E. face, with a mound of stone, 2½ ft. base, 1 ft. high, W. of corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 16 S R 27 E
S 27 S 26
S 34 S 35
1975

from which new bearing trees

A juniper, 8 ins. diam., bears N. 64° E., 140 lks. dist., mkd. T16S R27E S26 BT.

A juniper, 15 ins. diam., bears S. 33¾° W., 165 lks. dist., mkd. T16S R27E S34 BT.

and a bearing object

A basalt rock in place, 5 x 2½ x 2½ ft. above ground, bears S. 34° E., 39 lks. dist., mkd. X B0.

Deposit corner stone alongside iron post.


Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of corner.

RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 12, 2010

BY: 



November 11, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.