


CORNER RESTORATION

CORNER: NW Cor. Sec. 36 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: *Set basalt Stone 16x8x7 ins. 12 ins. in ground for cor to Secs 25, 26, 35 & 36.
Raised Mound of Stone 2½ ft. high and 4½ ft. at base alongside*

► 1975:

The cor. of secs. 25, 26, 35, and 36, monumented with an unmarked stone, 16 x 8 x 7 ins., loosely set in a mound of stone, 2½ ft. base, 1 ft. high.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T 16 S R 27 E
S 26 S 25
S 35 S 36
1975

from which

A juniper, 12 ins. dian., bears N. 68¼° E., 73 lks. dist., mkd. T16S R27E S25 BT.

A juniper, 12 ins. diam., bears S. 54° E., 47 lks. dist., mkd. T16S R27E S36 BT.

A ponderosa pine, 11 ins. diam., bears S. 77¾° W., 78 lks. dist., mkd. T16S R27E S35 BT.

A ponderosa pine, 12 ins. diam., bears N. 18° W., 69 lks. dist., mkd. T16S R27E S26 BT.

Deposit corner stone alongside iron post.


RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 12, 2010

BY: 



EXPIRES: 6/30/2012

November 11, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.