


CORNER RESTORATION

CORNER: W1/4 Cor. Sec. 33 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set basalt Stone 15x6x5 ins. 10 ins. in ground for 1/4 Sec. Cor. Marked 1/4 on W. face. From which a Pine 12 ins. diam. bears N1°E, 50 lks. dist. Marked 1/4 S BT, A Juniper 8 ins. diam. bears N30°W, 51 lks. dist. Marked 1/4 S BT.

- 1975: The 1/4 sec. cor. of secs. 32 and 33, monumented with the original basalt stone, 10 x 6 x 4 ins., loosely set 2 ins. in the ground, mkd. 1/4 on W. face, from which the remains of the original bearing trees:

A sawed pine stump, size indeterminate, bears N. 5° E., 50 lks. dist., with a pine log alongside, 24 ins. diam., with scribe marks 1/4 S visible on opened blaze. (Record, N. 10° E.)

A sawed juniper stump, 10 ins. diam., bears N. 32° W., 51 lks. dist., with scribe marks S B visible on opened blaze. (Record, N. 30° W.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 16 S R 27 E
1/4
S 32 | S 33
1975

from which new bearing trees

A ponderosa pine, 28 ins. diam., bears N. 72 1/2° E., 11 lks. dist., mkd. 1/4 S33 BT.

A juniper, 10 ins. diam., bears S. 64 3/4° W., 41 lks. dist., mkd. 1/4 S32 BT.

Deposit corner stone and set a juniper post, 3 ins. square, 3 ft. long, alongside iron post.


RESTORATION BY, STAMP AND DATE:

Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

DEC 3 2010

BY:



EXPIRES: 6/30/2012

November 30, 2010

Grant County Surveyor

EVIDENCE FOUND: None. No field visit was made for this Corner Restoration Report, it is prepared from record information. See Record Map of Survey No. 889 filed in the office of the Grant County Surveyor.