


CORNER RESTORATION

CORNER: W1/4 Cor. Sec. 36 Twp. 16 S. Range 27 E., W.M.

ORIGINAL SURVEY BY: Samuel W. Lackland

CONTRACT NUMBER: 415

CONTRACT DATE: August 19, 1881



Subsequent surveys:

- Gary Oviatt & Wayne Rogers in 1975 under special instructions dated August 25, 1975, Survey/Group No. 882

ORIGINAL DESCRIPTION: Set Post 4 ft. long, 4 ins. Square 12 ins. in ground for 1/4 Sec. Cor. Marked 1/4 S on W. face. From which A pine 40 ins diam. bears S80°E, 21 lks. dist. Marked 1/4 S BT. A Pine 10 ins. diam. bears N76°W, 20 lks. dist. marked 1/4 S BT.

► 1975:

The 1/4 sec. cor. of secs. 35 and 36, determined at record distance from the face of the original bearing trees:

A sawed ponderosa pine, 40 ins. diam., bears S. 76° E., 22½ lks. dist., with scribe marks 1/4 S B visible on open blaze. (Record, S. 80° E., 21 lks.)

A ponderosa pine, 21 ins. diam., bears N. 67° W., 21½ lks. dist., with healed upper blaze, no marks visible on opened lower blaze. (Record, N. 76° W., 20 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 16 S R 27 E
1/4
S 35 | S 36
1975

from which a new bearing tree


A ponderosa pine, 23 ins. diam., bears N. 43¾° E., 199 lks. dist., mkd. 1/4 S36 BT.

RESTORATION BY, STAMP AND DATE:


Michael C. Springer, PLS

RECEIVED AND FILED
GRANT COUNTY SURVEYOR

NOV 12, 2010

BY: 

REGISTERED
PROFESSIONAL
LAND SURVEYOR


OREGON
JULY 9, 2002
MICHAEL C. SPRINGER
#70918

EXPIRES: 6/30/2012

November 11, 2010

Grant County Surveyor

EVIDENCE FOUND: None. This Corner Restoration Report is prepared from record information.