

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1880 by Bamford Robb, under General Land Office Joint Contract No. 366.

Surveyor General's records state:

Set Stone 14x10x6 in mound of stone for $\frac{1}{4}$

Section Corner from which a pine 8" diameter bears S88°W 7 lks dist.

DIAGRAM

T16S $\frac{1}{4}$ R28E

$\frac{S8}{S17}$

$\frac{1}{4}$

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location, I found 14x10x6 in. stone 4 in. below top of ground with 2 smaller stones, called stone is not marked, from which an 8" pipe completely grown over bears S88°W 7 lks dist... Removed sufficient amount of overgrowth, orig. BT now 14" dia., to verify scribing. stone is 5.4 feet 8.3 lks. from face of bearing tree

Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence vicinity of corner agrees with original GLO record, at the location of the found 14x10x6 inch stone, I set a 30 inch long and 2 inch dia. galv. iron pipe in ground, in a mound of stones, with a 2 inch brass cap marked:

T16S R28E

$\frac{1}{4} \frac{S8}{S17}$

1978

PLS 1067

New Bearing Trees:

A Mahogany 5" dia. bears N54°30'E 41.8 feet
dist. scribed $\frac{1}{4}$ S 8 BT

I buried the 14x10x6 stone alongside the iron pipe and I placed USFS signs on the bearing strees. Set a 6' iron post with Attn. sign 5'E of corner-placed brass washers on BT's. I hereby certify the above corner monument was re-established as

herein described on June 7, 1978, witnesses: Johnny D. Smith

Darryl J. Anderson

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Sherman E. Anderson
OREGON
JULY 20, 1976
SHERMAN E. ANDERSON
1067

Office of..... *Surveyor* County of..... *Grant*
State of..... *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the..... *14* day of..... *Sept*....., 19.. *78*
Robert D. Engelt by.....
(COUNTY OFFICIAL) (DEPUTY)