

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1880 by Bamford Robb, under General Land Office Joint Contract No. 366. Surveyor General's records state:

Set stone 20x12x4 ins., in mound of stone for cor. to secs. 8, 9, 16, & 17 from which a:

Pine 10 in. dia. bears S 68°W, 80 links dist.

**DIAGRAM**

|      |      |
|------|------|
| T16S | R28E |
| S8   | S9   |
| S17  | S16  |

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location, I found a 16" P.P.B.T., original dia. 10", Remove grown over face and found scribing: T16S R28E S17. Did not remove growth over B.T. face.

Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence in vicinity of corner agrees with original GLO record, at the location of record bearing and distance from Bearing Tree, I set a 30"x2" iron pipe with brass cap, in a mound of stone, with brass cap marked:

|          |      |
|----------|------|
| T16S     | R28E |
| 1978     |      |
| S8       | S9   |
| S17      | S16  |
| PLS 1067 |      |

New Bearing Trees:

A Mahogany, 9" dia., bears N68°30'E 23.8 ft. dist., scribed: S 9 T16 R28E B.T. with brass washer marked 1067

A Mahogany, 5" dia., bears S37°30'E 44.8 ft. dist., scribed: S16 T16S R28E B.T. with brass washer nailed below 14" mark marked 1067

Placed USFS B.T. and Attn. signs on all Bearing Trees.

I hereby certify the above corner monument was re-established as herein described on June 1, 1978, witnesses: Johnny D. Smith

Assistant

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

OREGON  
JULY 30, 1976  
SHERMAN E. ANDERSON  
1067

Office of Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 31 day of Sept, 1978  
Robert D. Baggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)