

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1880 by Bamford Robb, under General Land Office Joint Contract No. 366.

Surveyor General's records state:

Set stone in mound of stone for corner to sections 19,20,29 & 30 from which;

A pine, 46 in. dia. bears N46°W, 58 lks. dist.

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location I found a 46 in. dead and down pine lying on face. I sawed out a piece and found face with scribing S19 T16S R28. I did not find stone or mound of stone anywhere in area.


Description of monument and accessories I established to perpetuate the original location of this corner:

As evidence in vicinity of corner agrees with General Land Office original record, at the location of record call and distance from original bearing tree, I set a 30 in. aluminum cap marked:


T18S	R28E
S19	S20
S30	S24
PLS 1067	
1978	

I set the following New Bearing Trees;

8" pine, bears N37° 30'W, 10.7 ft. dist.
scribed T18S R28E S20 BT
12" pine, bears S13°W, 44.4 ft. dist.
scribed T18S R28E S30 BT
20" pine, bears N61° 30'E 51.9 ft. dist.
scribed T18S R28E S14 BT
14" pine, bears S45° 30'E 19.5 ft. dist.
scribed T18S R28E S29 BT



Sherman E. Anderson



I placed brass washer marked PLS 1067 and USFS signs on all BT's. I hereby certify the above corner monument was re-established as herein described on July 7, 1978.

Witnesses: Darryl J. Anderson
Terry Butler

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*31*..... day of.....*Sept*....., 1978
.....*Robert D. Baggett*..... by.....
(COUNTY OFFICIAL) (DEPUTY)