

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1880 by Bamford Robb, under General Land Office Joint Contract No. 366.

Surveyor General's records state:

Set stone 16x10x10 in mound of stone for cor. to secs. 21,20,29 & 28 from which a pine 48 inch dia. bears S21°E 50 lks dist.

DIAGRAM

T16S	R28E
S20	S21
S29	S28

Note: No restoration appears in County records.

Description of corner evidence found:

At assumed corner location, I found 9x9x14 in. stone projecting 12 in. above ground with an X on top, from which a P. pine 50 in. dia. bears S 21° E 50 lks dist. with scribing visible on open face. S 28 T16S R28E. BT face overgrown.

Description of monument and accessories I established to perpetuate the original location of this corner:

As the evidence of corner bearing tree agrees with the original GLO records, I set a 30x2 in. galv. iron pipe at record call bearing and distance, with a 2 in. brass cap marked:

T16S R28E

S20	S21
S29	S28

1978

PLS 1067


New Bearing Trees:

A juniper, 7 in. dia. bears S 60° W 23.9 feet Scribed S 29 T16S R28E BT


A juniper, 5 in. dia. bears N 70° W 40.4 feet Scribed S 20 T16S R28E BT. A brass washer was placed 2 feet above ground on west face. A 2 foot snag is below scribed face. A 6 in. P. pine bears N 36° 30' E 35.4 feet dist. scribed S 21 T16S R28E BT.

I placed the found stone alongside the iron pipe and placed brass washer marked 1067 on all BT's, placed USFS B.T. and Attn. signs on all bearing trees. I hereby certify the above corner monument was re-established as herein described on June 1, 1978

Witness: Johnny D. Smith
Assistant



Sherman E. Anderson



Office of *Surveyor* County of *Grant*
State of *Oregon*, I hereby certify that the within instrument was filed in this office
for record on the *21* day of *Sept*, 19 *78*
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)