


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Closing Corner



History of original corner establishment:

Corner originally established by S. W. Lackland, under joint contract #357, dated July 2, 1880.

Surveyor General's records state: Set post from which; a pine 20" in diameter bears S 40°W 42 links distance a pine 16" in diameter bears S 85°E 31 links distance

Description of corner evidence found:

Found no evidence of original post.

Found 17" diameter burnt bearing tree, S 46°W 42 links distance, scribed "CC"

Found 15" diameter snag, S 78°E 31 links distance, scribed "CC" "BT"

Description of monument and accessories I established to perpetuate the original location of this corner:


Set 2½"x30" aluminum pipe with ¾" aluminum cap 26" in ground. Cap marked;

Bearing trees

a ponderosa pine 15" in diameter bears S 26½°W 57.6 feet distance, scribed "T16SR30ES6CC" in upper blaze and "ET" and brass tag stamped RLS 1664 in lower blaze.

a ponderosa pine 13" in diameter bears S 24°E 12.4 feet distance, scribed "T16SR30ES5CC" in upper blaze and "ET" and brass tag stamped RLS 1664 in lower blaze.

Compass declination 18° East



Note

I set a steel fence post with USFS Attention sign at corner, placed USFS bearing tree signs on all bearing trees, and painted red band on smooth bark at breast height on all bearing trees.

I hereby certify the above corner location was perpetuated as herein described on June 19, 1981.

Terry Butler Terry Butler, Witness

REGISTERED PROFESSIONAL LAND SURVEYOR

Carl E. Sundet
OREGON
JULY 14, 1978
CARL E. SUNDET
1664

Office of Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 23 day of Oct, 1981
Robert D. Buzitt by _____
(COUNTY OFFICIAL) (DEPUTY)