


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S. W. Lackland under joint contract number 357 dated July 2, 1880.

The government field notes state:

40.00 Set post for 1/4 sec. cor. with pit & mound from which
A pine 40 in dia bears S20°E 125 lks. dist



Description of corner evidence found:

I did not find the original corner post or Pits and mound.
I re-establish the corner position measuring from the face of the original bearing tree. From the corner point:

A 41 dia. PP stump bears S20°E 83.8 Ft. scribed /4S.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
24" in ground & erected a mound of stones around it.

from which I scribe NEW BEARING TREES:

A 23" DBH PP bears N27°W 236.8 Ft.,
scribed 1/4 S20 BT.
A 16" DBH PP bears N41°E 233.4 Ft.,
scribed 1/4 S21 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S R30E
1/4
S20 | S21
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.

I drove a 6 Ft. long steel fence post 2.5 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.

I used a steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.

This corner was set November 20, 1979.

Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of County Surveyor County of Grant
 State of Oregon , I hereby certify that the within instrument was filed
 in this office for record on the day of , 19
 by
 (COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR
F. E. Calkins
OREGON
JULY 13, 1979
F. E. CALKINS
1805