

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner has not been previously set.

DIAGRAM

T16S R30E

NW1/16+S28

1986
PLS 699

Description of corner evidence found:
Corner is being set by this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 3 1/4" aluminum cap, marked as shown in the diagram, 24" in the ground, at a point as determined by the procedures set forth in the MANUAL OF INSTRUCTIONS FOR THE SURVEY OF PUBLIC LANDS for the subdivision of sections. Built a mound of earth & rock to be 24" in diameter by 6" high around the monument, from which new BTs are:

10" Ponderosa pine bears S17° 15'W, 87.8 feet scribed NW1/16 S28 BT

7" Ponderosa pine bears S55°W, 148.3 feet scribed NW1/16 S28 BT

Attached BT and Land Survey Monument signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation, to stamped brass washers nailed in the scribed red-painted blazes. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground. Set steel fence posts 5 feet W and 5 feet S of the corner on the National Forest property lines. Attached Forest Boundary signs to each post and a Land Survey Monument sign to the W post.

I, Leland L. Myers, P.O. Box 98, Sumpter, OR 97877,
do hereby certify that on June 17, 1986, I established
the corner as herein described.

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

**OREGON
JULY 9, 1963
LELAND LEE MYERS
699**

Leland L. Myers

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR
THIS 30 DAY OF Sept, 1986

Robert D. Payne
Grant County Surveyor