


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S.W. Lackland under joint contract number 384 dated March 29, 1881.

The government field notes state:

40.00 Set stone 14 x 6 x 6 in mound of stone for 1/4 sec cor from which
A pine 30 in. dia bears S30°E 46 lks dist.



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

I did not find the original stone or mound of stones as corner position fell in center skid road.

I re-establish the corner position measuring from the face of the original bearing tree.

from the corner point:

A 34" DBH PP bears S30°E 46 lks. scribed BT in blaze that I opened. I count 93 growth rings since tree was scribed.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:

27" in ground & erected a mound of stones around it.

from which I scribe NEW BEARING TREES:

A 15" DBH White fir bears N21-1/2°E 28.7 Ft., scribed 1/4 S4 BT.

A 12" DBH Doug-fir bears N13°W 82.9 Ft., scribed 1/4 S5 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S R32E
1/4

S5 | S4
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.

I drove a 6 Ft. long steel fence post 3.1 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.

I used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.

This corner was set December 13, 1979.

Witness: F.R. Palmer.

Office of _____ County Surveyor _____ County of _____ Grant _____
State of _____ Oregon _____, I hereby certify that the within instrument was filed
in this office for record on the _____ day of _____, 1980
Robert D. Bayart by _____
(COUNTY OFFICIAL) (DEPUTY)

