


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 470 dated April 14, 1883.

Page 164 & 165 of the government field notes state:

- 80.00 Set a basalt stone 14 x 14 x 7 ins 9 ins in the ground for cor to secs 7, 12, 13 & 18; marked with 2 notches on the N. and 4 notches on the S. edges from which
- A pine 30 ins diam bears N51°E 48 lks. dist. marked T16S R33E S7 B.T
 - A pine 18 ins diam bears S44°E 46 lks dist marked T16S R33E S18 B.T
 - A pine 36 ins diam. bears S45°W 39 lks dist marked T16S R32E S13 B.T
 - A pine 16 ins. diam. bears N45°W 66 lks dist. marked T16S. R32E. S.12 B.T.



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 12" x 10" x 5" with 2 notches on N face & 4 notches on south face.

- Remnants of PP stump bears N51°E 48 lks. scribed T16S R33E S7 BT.
 " of down PP " N45°W 66 lks. " T16S R32E S12 BT.
 A 18" PP stump 2 ft. tall bears S45°W 39 lks. scribed 13S BT.
 Remnants of PP stump bears S44°E 46 lks. scribed 18 BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. iron pipe with brass cap marked:
 21" in ground & erected a mound of stones to top of cap. I buried the original corner stone flush with the ground on the N side of the new monument.
 from which I scribe NEW BEARING TREES:

- A 9" DBH PP bears N60°E 18.0 Ft., scribed T16S R33E S7 BT.
- A 7" DBH LPP bears N32-1/2°W 73.4 Ft., scribed T16S R32E S12 BT.
- A 11" DBH PP bears S34-1/2°W 71.0 Ft., scribed T16S R32E S13 BT.
- A 6" DBH PP bears S29-1/2°E 23.5 Ft., scribed T16S R33E S18 BT.

Painted faces & bands around BT's red & attached BT & Attention tags.
 Drove a 6 Ft. long steel fence post 2 Ft. in ground 2.7 Ft. North of corner & attached an attention tag to it.
 Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
 This corner was set August 20, 1979.
 Witness: F.R. Palmer, S. Anderson & L.R. Nevill

T16S	
R32E	R33E
S12	S7
S13	S18
1979	
OPLS	1805



Office of _____ County Surveyor _____ County of _____ Grant _____
 State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 5 day of Dec, 1979
 _____ by _____
 (COUNTY OFFICIAL) (DEPUTY)