


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S.W. Lackland under contract number 384 dated March 29, 1881.

The government field notes state:

40.00 Set stone 16 x 16 x 12 in mound of stone for 1/4 sec cor from which
A pine 36 in. dia. bears N47°E 15 lks dis.



Description of corner evidence found:

I did not find the original stone monument.
It could be in the large rock jack 3 feet south of the corner position. I re-establish the corner measuring from the face of the original bearing tree.
From the corner point:

A 32" DBH PP bears N47°E 15 lks. scribed 1/4S BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
25" in ground.
from which I scribe NEW BEARING TREES:

An 11" DBH PP bears S44°W 19.7 Ft.,
scribed 1/4 S16 BT.
A 14" DBH PP bears S48°E 51.8 Ft.,
scribed 1/4 S15 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S R32E
1/4

S16 + S15
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.
I drove a 6 Ft. long steel fence post 2.4 Ft. in ground 15 Ft. N of corner & attached an attention tag to it.
I used a steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set December 4, 1979.
Witness: F.R. Palmer

Office of _____ County Surveyor _____ County of _____ Grant _____
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 4 day of Feb, 1980
Robert D. Goyett by _____
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 13, 1979
F. E. CALKINS
1805