


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S.W. Lackland under joint contract number 384 dated March 29, 1881.

The government field notes state:

40.01 Set stone 24 x 16 x 6 in mound of stone for 1/4 sec. cor



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 20" x 16" x 6" marked 1/4 in a mound of stones.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:

15" in ground & erected a mound of stones around it. I placed the original stone monument face down, top to N, on the west side of the new monument on top of ground.

from which I scribe NEW BEARING TREES:

A 15" DBH PP bears N50°E 10.6 Ft., scribed 1/4 S17 BT.

A 13" DBH PP bears S8°E 27.6 Ft., scribed 1/4 S20 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S R32E
S17
1/4 ———
S20
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.

I drove a 6 Ft. long steel fence post 2.8 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.

I used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.

This corner was set December 14, 1979.

Witness: F.R. Palmer

Office of _____ County Surveyor _____ County of _____ Grant _____
State of _____ Oregon _____, I hereby certify that the within instrument was filed
in this office for record on the 4 day of Feb, 19 80
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

