


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S. W. Lackland under contract number 384 dated March 29, 1881.

Page 5 of the government field notes state:

80.00 Set stone 20 x 16 x 8 in mound of stone for cor to secs 15, 16, 21 & 22 from which
A pine 24 in dia bears N75°E 44 lks dist
" " 20 " " " S68E 54 " "



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 17" x 12" x 7" in a mound of stones from which:

A 27-1/2" DBH PP bears N76°E 44 lks. scribed S15 T16 R32 BT.
A 26" DBH PP bears S67°E 54 lks. scribed S22 T16 R32 BT.



Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
23" in ground & erected a mound of stones around it. I buried what appeared to be the original stone flush with the ground on the N side of the new corner monument.
from which I scribe NEW BEARING TREES:

A 11" DBH PP bears S64°W 14.6 Ft., scribed T16S R32E S21 BT.
A 10" DBH PP bears N78°W 33³ Ft., scribed T16S R32E S16 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB

T16S
R32E
S16 | S15
S21 | S22
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 2 Ft. in ground 6 Ft. north of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set September 5, 1979.
Witness: F.R. Palmer & L.R. Nevill

Office of _____ County Surveyor _____ County of _____ Grant _____
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 5 day of Dec, 1979
Robert D. Beyer by _____
(COUNTY OFFICIAL) (DEPUTY)