


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke
under contract number 494 dated January 16, 1884.

Page 52 of the government field notes state:

36.45 Set a basalt stone 18 x 14 x 12 ins
12 ins in ground for 1/4 sec cor
marked 1/4 on N face from which
A pine 20 ins dia bears N80°E 11 lks dist marked 1/4S BT
A pine 16 ins dia bears S78°E 14 lks dist marked 1/4S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 21" x 9" x 8" marked 1/4 on N face from which:

A 24" DBH PP bears S89°E 11 lks. scribed 4.
A 19" Dia. PP stump 12" high bears S63°E 14 lks. scribed BT.

Description of monument and accessories I established to perpetuate
the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe
with 3-1/4" cap marked:
22" in ground & erected a mound of stones
around it. I buried the original stone
face down top to N on the N side of the
new corner monument.
from which I scribe NEW BEARING TREE:

A 20" DBH PP bears S76°W 25.9 Ft., scribed
1/4 S22 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB

T16S
R32E

1/4 S15
S22
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 2 Ft. in ground 6 Ft. N of corner & attached
an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring
to the center of the new BT.
This corner was set September 6, 1979.
Witness: F.R. Palmer & L.R. Nevill

Office of _____ County Surveyor _____ County of _____ Grant _____
State of _____ Oregon _____, I hereby certify that the within instrument was filed
in this office for record on the 5 day of Dec, 19 79
Robert D. Sagert by _____
(COUNTY OFFICIAL) (DEPUTY)

FORM R6-7100-57 (9/71)

