


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 494 dated January 16, 1884.

Page 13 of the government field notes state:

3998 Set a basalt stone 16 x 10 x 10 ins
11 ins in ground for 1/4 sec cor marked
1/4 on N face from which
A pine 40 ins dia bears S24°E 39 lks dist
marked 1/4S BT
A pine 38 ins dia bears N74°W 60 lks dist
marked 1/4S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A red stone 15" x 10" x 9" marked 1/4 on N face from which:
A 36" DBH PP bears N74°W 60 lks. with good double scar.
A large burned PP stump bears S22°E 39 lks. scribed S BT.

Description of monument and accessories I established to perpetuate the original location of this corner:


Set a 30" long 2-1/2" dia. iron pipe with brass cap marked:

21" in ground & erected a mound of stones around it. I buried the original corner stone 2" below ground on the N side of the new monument.
from which I scribe NEW BEARING TREE:
A 9" DBH PP bears S58°W 33.5 Ft., scribed
1/4 S24 BT.

T16S
R32E

S13
—●—
S24
1979
OPLS 1805

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long iron fence post 2.3 Ft. in ground 6 Ft. north of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.
This corner was set August 28, 1979.
Witness: F.R. Palmer, S. Anderson & L.R. Nevill



Office of _____ County Surveyor _____ County of _____ Grant _____
State of _____ Oregon _____, I hereby certify that the within instrument was filed
in this office for record on the 5 day of Dec, 19 79
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)