


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by S. W. Lackland under contract number 384 dated March 29, 1881.

The government field notes state:

40.00 Set stone 18 x 16 x 3 in mound of stone for 1/4 sec cor from which
A pine 30 in dia bears N88°W 19 lks dist



Description of corner evidence found:

A stone 16" x 14" x 4" in mound of stones from which:

A 23" DBH PP snag bears N88°W 12.7 Ft. scribed 1/4S BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
21" in ground & erected a mound of stones around it. I buried the original stone monument on the North side of the new monument flush with the ground
from which I scribe NEW BEARING TREES:

A 14" DBH PP bears N83°W 32.6 Ft.,
scribed 1/4 S20 BT.
A 12" DBH PP bears S24°E 59.2 Ft.,
scribed 1/4 S21 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S R32E
1/4
S20 + S21
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

I painted faces & bands around BT's red & attached BT & Attention tags & nailed a brass washer to the new BT blaze marked PLS 1805.
I drove a 6 Ft. long steel fence post 2.4 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
I used a steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set December 10, 1979.
Witness: F.R. Palmer

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 4 day of Feb, 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

FORM R6-7100-57 (9/71)

