

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

None, this is a new corner.

DIAGRAM

T16S R32E

C 1/4
S26'

Description of corner evidence found:

Description of monument and accessories | established to perpetuate the original location of this corner:

Set a 3-1/4" x 28" aluminum monument 10" in the ground and erected a mound of stone around the monument.

7" Fir bears S62°W, 21.6 ft, scribed "C1/4S26BT",
with washer "LS 1918".

9" Fir bears S72-3/4°E, 7.9 ft, scribed "C1/4S26BT",
with washer "LS 1918".

T16S R32E
C 1/4
+
S 26
PLS 1918
1984

Painted faces and bands red on the BTs and attached Attention signs and BT tags. Set a steel fence post with Attention and Boundary signs North 3 ft.

This corner was set October 18, 1984.

Witnessed by: Louise H. Parsons.

Road Cadastral Survey, Cont. No. 53-04H1-4-9665N.

TYLER B. PARSONS
Professional Land Surveyor
1915 S.E. Stone Street
Corvallis, OR 97333
(503) 752-7515

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Tyler B. Parsons
OREGON
JULY 18, 1960
TYLER B. PARSONS
1918

Office of SURVEYOR County of GRANT
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 20 day of NOV, 1984
Robert A. Sapp by _____
(COUNTY OFFICIAL) (DEPUTY)