


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 494 dated January 16, 1884.

Page 6 of the government field notes state:

4000 Set a basalt stone 14 x 12 x 8 ins
10 ins in ground for 1/4 sec cor
marked 1/4 on W face from which
A pine 38 ins dia bears N50°E 49 lks dist
marked 1/4S BT
A pine 12 ins dia bears S70°W 37 lks dist
marked 1/4S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 14" x 8" x 5" marked 1/4 on west face from which:
A 33" DBH PP bears N50°E 49 lks. scribed 1/4S.
A 22" DBH PP stump 12" tall bears S70°W 37 lks. has scar on proper face & T
scar 5" in on top.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" dia. cap marked:
24" in ground & erected a mound of stones around it. I buried the original stone monument face down top to north flush with the ground on the north side of the new monument.
from which I scribe NEW BEARING TREE:
An 8" DBH PP bears S14°W 59.7 Ft.,
scribed 1/4 S26 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S
R32E
1/4
S26 ↓ S25
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long iron fence post 2 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.
This corner was set September 9, 1979.
Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of _____ County Surveyor _____ County of _____ Grant _____
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 4 day of Feb, 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

Supersedes remon. sheet filed Dec 6, 1979, by Calkins.

FORM R6-7100-57 (9/71)

