


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 494 dated January 16, 1884.

Page 62 of the government field notes state:

3716 Set a basalt stone 14 x 10 x 8 ins 9 ins in ground for 1/4 sec cor marked 1/4 on N face from which
A pine 30 ins dia bears N70°E 20 lks dist marked 1/4 S BT
A pine 36 ins dia bears S65°W 30 lks dist marked 1/4 S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 14" x 10" x 8" marked 1/4 on N face from which:


A 26" DBH PP bears S58°W 30 lks. scribed 1/4 B.
A 34" DBH PP bears N74°E 20 lks. scribed 1/4.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
21" in ground & erected a mound of stones around it. I buried the original stone monument flush with the ground, face down, top to north, on the N side of the new monument
from which I scribe NEW BEARING TREE:

A 9" DBH Doug Fir bears S44°W 10.6 Ft., scribed 1/4 S32 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S
R32E
S29
1/4
S32
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE



Painted faces & bands around BT's red, & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 2 1/4 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.

This corner was set September 13, 1979.

Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of _____ County Surveyor _____ County of _____ Grant _____
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 18 day of Dec, 19 79
Robert D. Rapp by _____
(COUNTY OFFICIAL) (DEPUTY)