


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 494 dated January 16, 1884.

Page 59 of the government field notes state:

3993 Set a basalt stone 16 x 16 x 12 ins 11 ins in ground for 1/4 sec cor marked 1/4 on N face from which
A pine 40 ins dia bears S15°W 47 lks dist marked 1/4 S BT
A pine 24 ins dia bears N18°E 70 lks dist marked 1/4 S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

I did not find the original corner stone.
I re-establish the corner measuring from the face of the only remaining original bearing tree. From the corner point:

A 33" DBH PP bears S15°W 47 lks. scribed 1/4 S.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" dia. cap marked:
8" above ground & erected a mound of stones around it.
from which I scribe NEW BEARING TREE:

An 11" DBH PP bears N52°E 66.7 Ft., scribed 1/4 S28 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S
R32E
S28
1/4 —•—
S33
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE



Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 2 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.
This corner was set September 12, 1979.
Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed
in this office for record on the 18 day of Dec, 1979
Robert D. Bantz by _____
(COUNTY OFFICIAL) (DEPUTY)

(Copy)