


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 494 dated January 16, 1884.

Page 45 of the government field notes state:

4006 Set a basalt stone 20 x 14 x 4 ins 15 ins in ground for 1/4 sec cor marked 1/4 on N face from which
A pine 40 ins dia bears N10°W 79 lks dist marked 1/4S BT
A pine 28 ins dia bears S12°E 63 lks dist marked 1/4S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

A stone 24" x 12" x 4" marked 1/4 on N face in mound of stones from which:
A 32" DBH PP bears S19°E 63 lks. (to face) scribed 1/4.
A 36" DBH PP snag 25 ft. tall bears N11°W 79 lks. (to face) with good double scar.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. aluminum pipe with 3-1/4" cap marked:
9" above ground & raised a mound of stones around it. I buried the original stone monument face down, top to North, on the N side of the new monument, flush with the ground. from which I scribe NEW BEARING TREE:

A 10" DBH PP bears N69°E 38.0 Ft., scribed 1/4 S27 BT.

U.S. DEPT.
OF AGRICULTURE
UNLAWFUL TO DISTURB
T16S
R32E
S27
1/4
S34
OPLS 1805
1979
CADASTRAL SURVEY
FOREST SERVICE

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 1-1/2 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT.
This corner was set September 10, 1979.
Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of _____ County Surveyor _____ County of _____ Grant _____
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 4 day of Feb, 1980
Robert D. Baggett by _____
(COUNTY OFFICIAL) (DEPUTY)

